



**BINDER VERSION**



**WF 1575 LH**

## Global WF 1575 LH Series WALKING FOOT CYLINDER ARM MACHINES

### WF 1575 LH

Single needle, cylinder arm, walking foot machine with a 6 mm stitch length and alternating foot stroke adjustment by dial. The machine is equipped with large vertical axis hook and is suitable to sew medium heavy leather. Manual lubrication.

Máquina de una aguja de brazo cilíndrico con, largo puntada 6 mm y regulador del salto de altura de la pata del prensatelas. Con garfio grande sobre eje vertical. Apropiaada para trabajos en cuero medio pesado. Lubricación manual.

Einnadel, Zylinderarm, Dreifachtransport Maschine mit 6 mm Stichlänge und Hubhöhenverstellung über Stellrad einstellbar. Die Maschine ist ausgestattet mit einen großen Vertikalgreifer und geeignet zum nähen von mittelschwerem Leder. Manuelle Schmierung.

Machine canon point noué une aiguille à triple entraînement avec longueur de point de 6 mm et réglage rapide de la course des pieds. Equipée de crochet grande capacité sur axe vertical et convient à la couture du cuir moyen et épais. Lubrification manuelle.

### WF 1575 B-LH

Same as WF 1575 LH, but equipped for binding work (binder not included).

Las mismas características que la WF 1575 LH, pero equipada para ribetear (embudo no incluido).

Baugleich mit WF 1575 LH, jedoch vorbereitet für Einfassarbeiten (ohne Einfasser).

Modèle identique à la version ci-dessus mais avec dispositif de bordage (guide bordeur non compris).

### TECHNICAL SPECIFICATIONS

**MACHINE SPEED**  
max 2500 spm

**OILING SYSTEM**  
oil wick lubrication  
(hook: manual)

**FEED TYPE**  
drop feed, needle feed  
walking foot

**INNER FOOT ADJUSTMENT**  
2,5 – 6,5 mm by dial

**PRESSER FOOT LIFT**  
by hand: max 9 mm  
by knee: max 16 mm

**NEEDLE BAR STROKE**  
36 mm

**NEEDLE TYPE**  
135x17  
Nm100-Nm180

**THREAD SIZE**  
up to 10