


Standard type

C=750 mm
D=115 mm



XL type

C=750 mm
D=165 mm



ZZ 9567-75 XL P-AUT

Optional cams!



Global ZZ 9567-75 Series LONGARM PATTERN ZIG-ZAG MACHINE

ZZ 9567-75

- Longarm pattern zig-zag machine with pneumatic back tack and electric presser foot lift. Standard delivered with 1 stitch pattern cam (three point zig-zag). Total 14 different pattern cams available. Semi-automatic lubrication. Working space: L x H = 750 x 115 mm.
- Máquina de cama larga zig-zag con remate neumático y alza-prensatejas eléctrico. De distintos patrones por disco que viene con 1 tipos de discos en total hay 14 discos disponibles. Lubricación semi-automática. Espacio de trabajo: L x A = 750 x 115 mm.
- Langarm Zick-Zack Maschine mit pneumatische Verriegelung und elektrischer Fußlüftung. Standard mit 1 Zierstich-Muster-Kurvenscheibe (Dreistich zick-zack). 14 Muster-Kurvenscheiben sind lieferbar. Durchgangsraum: L x H = 750 x 115 mm.
- Machine zig-zag grand bras avec commande pneumatique des arrêts et du relevage de pied électromagnétique. Livraison standard avec 1 came de points différents (zig-zag trois points). 14 comes de points disponibles en option. Lubrification semi-automatique. Surface de travail de: L x H = 750 x 115 mm.

ZZ 9567-75 AUT

- Same as ZZ 9567-75, but equipped with electric underbed trimmer, pneumatic back tack and presser foot lifter.
- Mismas características que la anterior, pero equipada con corta-hilo eléctrico y remate y alza-prensatejas por neumático.
- Baugleich mit ZZ 9567-75, jedoch ausgestattet mit automatischem Fadenabschneider (elektrisch) und pneumatische Fußlüftung und Verriegelung.
- Identique à la ZZ 9567-75, mais avec coupe fil électromagnétique, et commande pneumatique des arrêts et du relevage de pied.

ZZ 9567-75 P

- Same as ZZ 9567-75, but equipped with puller.
- Mismas características que la ZZ 9567-75, pero equipada con puller.
- Baugleich mit ZZ 9567-75, jedoch ausgestattet mit Puller.
- Identique à la ZZ 9567-75, mais équipée avec un puller.

ZZ 9567-75 P-AUT

- Same as ZZ 9567-75 AUT, but equipped with puller and pneumatic puller lifter.
- Mismas características que la ZZ 9567-75 AUT, pero con puller y alza- puller neumático.
- Baugleich mit ZZ 9567-75 AUT, jedoch ausgestattet mit Puller und pneumatische Pullerlüftung.
- Identique à la ZZ 9567-75 AUT, mais équipée avec un puller et d'une commande pneumatique de relevage du puller.

ZZ 9567-75 XL-P-AUT

- Same as ZZ 9567-75 P-AUT, but with higher working space: L x H = 750 x 165 mm.
- Mismas características que la ZZ 9567-75 P-AUT, pero con el espacio de trabajo: L x A = 750 x 165mm.
- Baugleich mit ZZ 9567-75 P-AUT, jedoch mit größere Durchgangsraum: L x H = 750 x 165 mm.
- Identique à la ZZ 9567-75 P-AUT, mais avec une surface de travail de: L x H = 750 x 165 mm.

TECHNICAL SPECIFICATIONS

MACHINE SPEED
max 1400 spm

OILING SYSTEM
Semi automatic

STITCH LENGTH
max 5 mm

PRESSER FOOT LIFT
max 12 mm

ZIG-ZAG WIDTH
max 10 mm

NEEDLE TYPE
134 R

STITCH TYPE
Three point zig-zag



NOTE
To use this machine, you need a servo motor